

Email: info@baski.com Website: www.baski.com Manufacturer of Inflatable Packers, Flow Control Valves, Pitless Units and other products for investigating, controlling and producing the EARTH'S FLUIDS.TM

Phone: 1-303-789-1200 • 1-800-55-BASKI

FAX: 1-303-789-0900

SPECIFICATION SHEET:

FrackerTM Model FR-4.9

Sliding-Head Type Packer (USA Pat. No. 4,455,027)

Dimensions and Confined/Unconfined Test Pressures:

| Uninflated O.D., max. | 4.9" | 124 mm |
|--------------------------------------|-----------|----------|
| Largest recommended hole size | 7.0" | 178 mm |
| Approximate mandrel pipe O.D. | 2" | 51 mm |
| Approximate mandrel pipe I.D. | 1.25" | 32 mm |
| Uninflated element length, min. | 45" | 1,143 mm |
| Tested unconfined to | 3,000 psi | 207 bar |
| Tested confined in a 6" I.D. pipe to | 4,000 psi | 276 bar |

Differential Pressure Rating (DPR): in single packer applications, for specific hole sizes

| Inside di | ameter | Pres | sure | Maxi | mum | Maxi | mum |
|-----------|--------|----------|------------|------------|-------------|----------------|---------------|
| of cas | sing | to st | retch | borehole d | ifferential | inflation pres | sure over the |
| or bore | ehole | rubber (| element | pressure | e rating | packer sub | mergence |
| inches | mm | psi | <u>bar</u> | psi | bar | psi | <u>bar</u> |
| 5.5 | 140 | 50 | 3 | 3,200 | 221 | 4,000 | 276 |
| 6.0 | 152 | 75 | 5 | 3,000 | 207 | 3,600 | 248 |
| 6.25 | 159 | 90 | 6 | 2,800 | 193 | 3,300 | 227 |
| 6.5 | 165 | 115 | 8 | 2,600 | 179 | 3,100 | 214 |
| 7.0 | 178 | 280 | 19 | 2,000 | 138 | 2,600 | 179 |

Please call factory for DPR in straddle packer applications.

Construction and Materials:

| Element | Construction | Fully-reinforced (reinforcing the entire length of element) | | | |
|---------|--------------------|---|--|--|--|
| | Materials | Aramid reinforced natural rubber, with | | | |
| | | outer covering of natural rubber | | | |
| | Connection to ends | 14" (356 mm) high strength steel Continuous Crimp Collar | | | |
| Heads | Top | Stainless steel, with 1/4" (6 mm) NPT inflation ports | | | |
| | Bottom | Stainless steel, with Dirt Wiper TM and 1/4" (6 mm) NPT inflation port | | | |
| Mandrel | Pipe | 2.375" (60 mm) O.D., 3/8" (9 mm) wall | | | |
| | Material | high strength steel tubing, high phosphate electro-less nickel plated | | | |
| | Connection | API 2.375" (60 mm) non-upset tubing thread, 10 round pattern, | | | |
| | | top and bottom | | | |

Accessories:

| Replacement Element | Model FRE-4.9 | the replacement element for our Fracker TM FR-4.9 | | |
|--------------------------|-------------------------|--|----------|--|
| Frac pipe, high strength | supplied in 10' lengths | 2" nominal, used to connect straddle packers | | |
| Shipping Data: | Approx. net weight | 180 lbs. | 80 kg | |
| | Approx. net length | 95" | 2,400 mm | |

Pricing and Terms: Please call for pricing, FOB Denver factory and valid for 60 days.

Approx. net length

Our terms are prepay (wire transfer, Visa, MasterCard, or certified check).

Company checks require approximately two (2) weeks to clear.