

Email: <u>info@baski.com</u>
Website: www.baski.com

Valves, Pitless Units and other products for investigating, controlling and producing the EARTH'S FLUIDS.TM

Phone: 1-303-789-1200 • 1-800-55-BASKI

FAX: 1-303-789-0900

SPECIFICATION SHEET:

Packer Model MD-4.5

Medium Duty, Sliding-Head Type (USA Pat. No. 4,455,027)

Manufacturer of Inflatable Packers, Flow Control

Dimensions and Confined/Unconfined Test Pressures:

Uninflated O.D., max.	4.5"	114 mm
Largest recommended hole size	8.5"	216 mm
Mandrel pipe size, nominal	2"	51 mm
Approximate mandrel pipe I.D.	1.94"	49 mm
Uninflated element length, min.	40"	1,016 mm
Tested unconfined to	500 psi	35 bar
Tested confined in a 6" (152 mm) chamber to	1,000 psi	70 bar

Differential Pressure Rating (DPR): in single packer applications, for specific hole sizes

Cased or		Maximum	
Competent		Differential	
Hole Size		Pressure Rating	
inches	mm	psi	bar
5.5	140	1,000	70
6.0	152	1,000	70
6.5	165	800	55
7.0	178	600	40
8.0	203	400	30
8.5	216	350	25

Please call factory for DPR in straddle packer applications.

Construction and Materials:

Element	Construction	Fully-reinforced (reinforcing the entire length of element)
	Materials	Reinforced natural rubber, with
		outer covering of natural rubber
	Connection to ends	11" (279 mm) Type 316 stainless steel Continuous Crimp Collar
Heads	Connection	1/4" NPT inflation ports, top and bottom
Mandrel	Pipe	2" Schedule 80 pipe
	Material	Type 316 stainless steel
	Connection	2" NPT, top and bottom
Other	Metal Parts	Type 316 stainless steel

Accessories:

In-Line Adapter	Model ILA2.0	2" nominal pipe size, Aluminum, 8 top ports
		Includes an assortment of brass fittings for sealing
		electrical leads in varying diam., 3/16", 1/4", 3/8"

Shipping Data:	Approx. net weight	91 lbs.	41 kg
	Approx. net length	84"	2,134 mm

Pricing and Terms: Please call for pricing, FOB Denver factory and valid for 60 days.

Our terms are prepay (wire transfer, Visa, MasterCard, or certified check).

Company checks require approximately two (2) weeks to clear.

updated May 20, 2004 specifications subject to change without notice MD45_specs_rev6b