

Manufacturer of Inflatable Packers, Flow Control Valves, Pitless Units and other products for investigating, controlling and producing the EARTH'S FLUIDS.TM

Phone: 1-303-789-1200 • 1-800-55-BASKI FAX: 1-303-789-0900

Packer Model MD-6.2

SPECIFICATION SHEET:

Medium Duty, Sliding-Head Type (USA Pat. No. 4,455,027)

Dimensions and Confined/Unconfined Test Pressures:		
Uninflated O.D., max.	6.2"	157 mm
Largest recommended hole size	12.0"	305 mm
Mandrel pipe size, nominal	3"	76 mm
Approximate mandrel pipe I.D.	2.50"	64 mm
Uninflated element length, min.	50"	1,270 mm
Tested unconfined to	500 psi	34 bar
Tested confined in a 9.75" (248 mm) chamber to	1,000 psi	68 bar

Differential Pressure Rating (DPR): in single packer applications, for specific hole sizes

Inside di	ameter	Pres	sure	Maxi	mum	Maxi	mum
of cas	sing	to str	retch	borehole d	lifferential	inflation pres	sure over the
or bore	ehole	rubber e	element	pressure	e rating	packer sub	mergence
inches	mm	psi	bar	psi	bar	psi	bar
7.0	178	20	1.5	1,000	68	1,500	102
8.0	203	30	2	1,000	68	1,500	102
9.0	229	40	3	800	54	1,250	85
10.0	254	60	4	600	40	1,000	68
11.0	280	80	5	500	34	900	61
11.5	292	100	7	400	27	800	54
12.0	305	150	10	300	20	600	40

Please call factory for DPR in straddle packer applications.

Construction and Materials:

Constituct	ion and mate	1 101.5.				
Element Construction		Fully-reinforced (reinforcing the entire length of element)				
	Materials		Reinforced 1	natural rubber, with outer coverin	ng of natural rubber	
	Connection to	ends	17" (432 mm) high strength steel Continuous Crimp Collar			
Heads	Connection		3/8" NPT inflation ports, top and bottom			
Mandrel	Pipe		3" nominal			
	Material		high strength steel, high phosphate electroless nickel OD plating			
	Connection		standard with 3.5" O.D. NUE thread, top and bottom			
Accessorie	es:					
Replacement Element		Model MDE-6.2		the replacement element for our MD-6.2		
In-Line Ada	apter	ter Model ILA3.0 3" nominal pipe		3" nominal pipe size, Aluminu	m, 8 top ports	
	•			Includes an assortment of bras	s fittings for sealing	
				electrical leads in varying dian	neters: 3/16", 1/4", 3/8"	
Shipping Data:		Approximate net weight		300 lbs.	140 kg	
11 8		Approximate	net length	130" x 11" x 15"	3.3m x 0.3m x 0.4m	
		11	U			
Pricing an	Pricing and Terms:Please call for pricing, FOB Denver factory and valid for 60 days.					
		Our terms are prepay (wire transfer, Visa, MasterCard, or certified check).				
		Company checks require approximately two (2) weeks to clear.				
updated Sept 20, 2011 specifications subject to cha		to change without notice	MD62_specs_rev6j.pdf			